

FF20U5

IP55 version without fan



FF series exhaust filter and filter fans represents a side-mounted cooling solution with filtered ambient air to maintain optimum ventilation inside the electrical cabinets. Screwless connection, fast tool-free mounting system with clip and maintenance friendliness are the main benefits. Available in a wide range of configurations for both indoor and outdoor use.

Technical data		
APPROVALS		
Approvals	CE; cURus; cULus; cCSAus	
MECHANICAL DATA		
Mounting Wall Thickness	1.3-3.7 0.05-0.15	mm in
GENERIC DATA		
Spare Parts Filter Media	M20FPF	
Casing Material	PC/ABS UL94 V-0	
RAL Number	7035	
Filter Class	ISO coarse 75%	ISO 16890
Filter Class	G4	EN 779
Filter Material	thermo-linked progressive structure synthetic fibre	
ENVIRONMENTAL AND THERMAL DATA		
IP Protection Degree	IP55	
Operating Temperature	-30÷60	°C
	-22÷140	°F
Storage Temperature	-40÷70	°C
	-40÷158	°F
UL DATA		
UL File Number Recognized Component	E237844	
UL File Number Listed	E500932	
UL Environmental Type Rating	Type 12	

FF20U5


IP55 version without fan

Technical data		
UL Ambient Temperature	60	°C
	140	°F

FF20U5

IP55 version without fan

Technical drawing mm (in)



Mounting cut-out mm (in)

