
## frame fans






Thermoplastic in black color, UL 94 V-0 Casing material: Impeller material Thermoplastic in black color, UL 94 V-0 Protection degree: IP20, according to EN 60529 standard

Fixing system: by No 4 M4 screws

Motor protection: Impedance

from -40°C to +75°C Storage temperature: from -30°C to +70°C Rated temperature range: ball bearing 50,000 h Lifetime L10 at 40°C: Electrical connection: 2 leads 24 AWG UL1430

Approvals: CE Weight: 0.270 kg







Model	Bearing	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Noise	RPM	Approvals
		(V)	(Hz)	(A)	(W)	(m3/h)	(Pa)	[db(A)]	(rpm)	
E12B23HWBL00	Ball	230 V a.c.	50/60	0.05/0.05	6.0/6.0	198/206	79/77	45.0/46.8	3,000/3,100	CE
E12B23LWBL00	Ball	230 V a.c.	50/60	0.03/0.03	2.5/2.5	132/138	32/37	34.0/35.7	2,000/2,100	CE
E12B23MWBL00	Ball	230 V a.c.	50/60	0.04/0.04	4.0/4.0	169/176	55/58	40.0/41.8	2,500/2,700	CE