



"A17TMT" SERIES COSTECH FANS



Casing material: Impeller material Protection degree: Fixing system: Insulation class: Motor protection: Storage temperature: Rated temperature range: Lifetime L10 at 40°C: Electrical connection: Approvals: Weight: Black varnished aluminum Metal IP44, according to EN 60529 standard by 2x No. 4 Ø4.3mm holes F thermal from -40°C to +90°C from -40°C to +90°C 40,000 h 2 leads 22AWG UL 3239, 350 mm long UL E223195 1.1 kg



Model	Bearing	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Noise	RPM	Approvals
		(V)	(Hz)	(A)	(W)	(m3/h)	(Pa)	[db(A)]	(rpm)	
A17T12SWBMT0	Ball	115 V a.c.	50/60	0.54/0.51	45/45	383/434	124/124	58.0/61.0	2,750/3,150	CE; cURus
A17T23SWBMT0	Ball	230 V a.c.	50/60	0.270/0.250	45/45	383/434	124/124	58.0/61.0	2,750/3,150	CE; cURus

All specifications, data and drawing are subject to change without notice. Please refer to our terms of sales including our warranty and limited liabilities clauses.