


C22SD SERIES

Description: **Axial fan a.c. 218X218X83mm**



Impeller material:

fibre reinforced plastic (PA66) blades

Casing material:

aluminium alloy die casting UNI5076

Fixing system:

No 4 holes Ø4.5

Motor protection:

thermal

Rated temperature range:

from -20°C to +70°C

Motor Lifetime L10 at 25°C (approx.):

63,000 h

Insulation class:

F




Working class of capacitor:

class B for 115V model
class A for 230V model

Electrical connection:

by screwless terminal block 2.5 mm² (20 - 14 AWG): 3 poles L-N-PE for 115/230Va.c. models; 4 poles L1-L2-L3-PE for 400Va.c. models
1,9 kg

Weight:



Model	Bearing	Voltage	Frequency	Rated Current	Rated Power	Max Air Flow**	Static Pressure	Noise	RPM	Approvals
		(V)	(Hz)	(A)	(W)	(m3/h)	(Pa)	[db(A)]	(rpm)	
C22S12HKBD00	Ball	115 V a.c.	50/60	0.79/0.83	79/96	855/930	190/201	64.6/67.4	2,490/2,760	CE
C22S23HKBD00	Ball	230 V a.c.	50/60	0.343/0.411	78/94	855/930	197/211	65.0/68.0	2,490/2,750	CE
C22S40HKBD00	Ball	400 V 3 ~	50	0.280	174	970	265	61.0	2,770	CE