


Location of Batch Code Label (on DE housing surface above power cable)



Location of Atex Label (on DE housing surface)

Location of Product Label (on NDE housing surface)

MOTOR RATING

PRODUCT CODE	Max Output Watts @ Corresponding rpm	Supply voltage, Frequency	DOR, Mode of Operation
ECR2-0571	13 Watts @ 1800 rpm	100-240Vac, 50-60Hz	CCW-DE Continuous, Speed Control 1400 rpm

Ex II 3 G, Ex nA IIA T4
T_{amb} -30°C to +60°C
US/UL/ExTR15.0133/00
 Do not open when energised

Atex Label

Wellington
ECR2-0571
 INPUT: 100-240Vac, 50-60Hz, 0.19-0.10A
 OUTPUT : 13W@1800rpm
 EP -30° to +50°C, DOR: CCW-DE
 Speed control 1400rpm

IP67
 -30° to +60°C Made in Vietnam

Product Label

Note:
 1. Motor rating Refer to table.
 2. Refer operating instructions for installation details.

ZONE	ISSUE	ECN	DESCRIPTION	DATE	DRAWN	CHECKED
B-5.7	4	WCP3511	Updated drive flange design	25/09/2019	ASo	MTi
A-5	3	WCP2315	Dim 34.5 +/-2 was 35.4 +/-2	07/06/2016	RDI	ASo
C-1	2	NA	Power cable length 2000 was 1200	07/04/2016	RDI	ASo

DO NOT SCALE OFF DRAWING

Wellington
 www.wdt.com

The information contained in this drawing is confidential. Reproduction of this document in any form is subject to explicit written permission.
 © COPYRIGHT 2004 - 2009 Wellington Drive Technologies Ltd

Description: **Dimensional Drawing**

Product Code: Refer to table above

Orthographic Projection: Third Angle

STATUS: **P**

Scale: **NTS** Dimension: **mm** Sheet size: **A3**

GENERAL TOLERANCE: **±1** ANGULAR: **±3°** DWG No.: **WD7864A** Sheet: **1 of 1**